This Page Is Inserted by IFW Operations and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents will not correct images, please do not report the images to the Image Problem Mailbox.

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6: B42D 15/00 A1 (11) International Publication Number: WO 98/03348 (43) International Publication Date: 29 January 1998 (29.01.98)

(21) International Application Number: PCT/NL97/00401

(22) International Filing Date: 9 July 1997 (09.07.97)

(30) Priority Data: 1003663 23 July

23 July 1996 (23.07.96) NL


(71)(72) Applicant and Inventor: SCHELL, Karel, Johan [NL/NL]; Voorstraat 60, NL-2201 HX Noordwijk (NL).

(74) Agent: DE BRUIJN, Leendert, C.; Nederlandsch Octrooibureau, Scheveningseweg 82, P.O. Box 29720, NL-2502 LS The Hague (NL). (81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).

Published

With international search report.

(54) Title: METHOD FOR PROTECTING A PAPER SECURITY DOCUMENT OR IDENTIFICATION DOCUMENT



(57) Abstract

In order to protect a paper-thin valuable document or identification document on which an identification mark has been placed, for example by means of a printing technique or by a laser technique, in such a way that counterfeiting is extremely difficult, at least part of said identification mark is repeated at another point by changing the thickness of the document locally. At least part of the identification mark is thus clearly linked to the paper substrate.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	Sì	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
ΑÜ	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IB	treland	MN	Mongolia	€A.	Ukraine
BR	Brazil	IL	Brael	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Eceland	MW	Malawi	US	United States of America
CA	Canada	ľT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
Cl	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

METHOD FOR PROTECTING A PAPER SECURITY DOCUMENT OR IDENTIFICATION DOCUMENT

The invention relates to a method for protecting a paper-thin valuable document or identification document on which an identification 5 mark has been placed.

The fact that all kinds of copying techniques have become available to the public means that it is becoming increasingly important to protect banknotes and documents permitting the identification of persons. Counterfeiting must become increasingly difficult, and 10 protection must always be ahead of the equipment available to the counterfeiter. Banknotes and passports or other identification documents always have a number or other specific mark by means of which they can be recognized as unique notes or documents.

The object of the invention is to provide a method of the type
15 mentioned in the preamble which leads to banknotes or identification
documents whose abovementioned unique number or mark, or part thereof, is
very difficult to counterfeit.

According to the invention, the method referred to in the preamble is characterized in that at least part of said identification 20 mark is repeated at another point by changing the thickness of the document locally.

The repeat of said identification mark or part thereof is preferably carried out by reducing the thickness of the document by means of laser etching.

Laser etching, which is carried out by local removal of, for example, slightly less than half the thickness of the paper or plastic, clearly links the identification mark or part thereof to the paper substrate. By local thinning of the paper or paper-thin plastic, security which is linked to the identification mark is provided.

25

30

No hologram, film or kinoform image is therefore added, but only substrate material is removed to a certain depth.

As a consequence of laser etching the part of the document having the locally reduced thickness, gets a brown colour, most likely caused by the fact that the energy rich laser beam burns the substrate a little bit. The brown coloured marks, which are dark with respect to the surrounding substrate, do not have the appearance of a water mark. Comparing the printed marks with the repeated marks becomes difficult.

By exposing the part of the document on which the repeated part

of the identification mark has been placed, to bleaching or decolouring, the brown colour vanishes. A pre-treatment with a bleaching or decolourizing agent, for instance by an impregnated pad, may take place immediately after the laser etching.

5

20

35

Oxidizing bleaching agents are for instance peroxides, hypochlorides, persalts such as potasiumpermanganate (KNMOb). potasiumpersulphate (K2S2O8), sodium perborate (NABO3), sodium percarbonate (NA_2CO_4) and ozon (O_3) . It is not excluded that the substrate itself comprises an oxidizing bleaching agent, in which case the 10 treatment with a bleaching agent immediately after the laser edging can be omitted.

The invention can be successfully used on a banknote, where the identification mark is the banknote number, and the repeated part of the identification mark obtained by changing the thickness of the document locally is the so-called check digit of the banknote number.

The invention also relates to a valuable document or identification document on which an identification mark has been placed. at least part of which is repeated by means of the method described above by changing the thickness of the document locally.

The invention will now be explained further with reference to the figure. This figure shows a copy of a banknote, on a slightly enlarged scale.

It can be seen in the figure that on the lower right-hand side the unique identification number 3681209430 is produced on the paper of 25 the banknote by means of a printing technique. The last two digits, 30. which are known by the term "check digit", are repeated at another point on the banknote by removing the paper over part of the paper thickness. preferably no more than half the paper thickness, by laser etching. Therefore, by local thinning, additional protection which is linked to 30 the existing mark is achieved. This local thinning constitutes an extremely great complication for a counterfeiter. The protection against counterfeiting has therefore been greatly improved by a simple trick. Instead of being made of paper, the banknote or the document can be made of plastic with the thickness and flexibility of paper.


Furthermore, it is quite possible for the identification number concerned to be applied by laser etching all the way through the paper, instead of by printing.

Methods other than laser etching for changing the thickness of the document locally, and repeating at least part of the identification

mark in this way, also fall within the scope of the inventive idea.

Claims

- 1. Method for protecting a paper-thin valuable document or identification document on which an identification mark has been placed, characterized in that at least part of said identification mark is repeated at another point by changing the thickness of the document.
- 5 repeated at another point by changing the thickness of the document locally.
 - 2. Method according to Claim 1, characterized in that the repeat of said identification mark or part thereof is carried out by reducing the thickness of the document by means of laser etching.
- Method according to claim 2, characterized in that said part of the document on which the repeated part of the identification mark has been placed, is exposed to bleaching or decolouring.
- Method according to one of the preceding claims, characterized in that the document is a banknote, in that the identification mark is
 the banknote number, and in that the repeated part of the identification mark obtained by changing the thickness of the document locally is the so-called check digit of the banknote number.
 - Valuable document or identification document on which an identification mark has been placed, at least part of which
- 20 identification mark is repeated by means of the method according to one of the preceding claims by changing the thickness of the document locally.



PCT	/NL	97/	/004	101
-----	-----	-----	------	-----

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 388090 A	19-09-90	DE 69017242 D DE 69017242 T HK 94696 A	06-04-95 29-06-95 07-06-96
DE 3634098 A	16-04-87	AT 386159 A CH 677290 A FR 2588509 A GB 2183544 A,B JP 62094377 A US 4740269 A	11-07-88 30-04-91 17-04-87 10-06-87 30-04-87 26-04-88
DE 4334847 A	20-04-95	AT 155742 T AU 681909 B AU 7738994 A BR 9407796 A CA 2163528 A CN 1131930 A WO 9510420 A DE 59403479 D EP 0723501 A HU 75148 A JP 9503711 T	15-08-97 11-09-97 04-05-95 18-03-97 20-04-95 25-09-96 20-04-95 28-08-97 31-07-96 28-04-97 15-04-97
WO 9526274 A	05-10-95	NL 9400498 A EP 0748286 A	01-11-95 18-12-96